Save up to 25%

Buy Online

PROTECTION *you demand.* | PERFORMANCE *you deserve.™*

DATA SHEET

SEVERE GEAR® 100% Synthetic Extreme-Pressure (EP) Gear Lube

Formulated for the severe operating conditions of today's pickup trucks, SUVs, heavy equipment and other hard-working vehicles.



AMSOIL SEVERE GEAR® 100% Synthetic Extreme-Pressure (EP) Gear Lube is a premium-grade gear oil specifically engineered for maximum performance in severe-duty applications. It maintains its viscosity for long-lasting protection against metal-to-metal contact. Its proprietary AMSOIL additives form an iron-sulfide barrier coating on gear surfaces, providing the ultimate line of defense against wear, pitting and scoring. AMSOIL SEVERE GEAR helps prevent "thermal runaway" – a phenomenon caused by a lubricant's inability to control friction and increased heat under high-stress conditions. By controlling thermal runaway, AMSOIL SEVERE GEAR 100% Synthetic EP Gear Lube inhibits rapid lubricant degradation and component damage – helping equipment run better and last longer.

Performance

AMSOIL SEVERE GEAR provides performance far beyond what is possible with conventional gear oil. We designed SEVERE GEAR to deliver superior gear and bearing protection, better friction and heat reduction, increased efficiency and extended service life.

Temperature Extremes

SEVERE GEAR excels in hot and cold temperature extremes. By design, it resists breakdown from high heat, preventing acid and carbon/varnish formation. Its wax-free construction also improves cold-flow properties, improving fuel economy and cold-weather shifting.

Applications

AMSOIL SEVERE GEAR is excellent for severe applications, such as towing, hauling, steep-hill driving, commercial use, plowing, racing, off-road use, rapid acceleration, frequent stop-and-go operation and high ambient temperatures. Higher horsepower, towing and hauling capabilities of modern vehicles make pickups, SUVs, vans and delivery/utility vehicles especially prone to severe service. Other severe-duty vehicles include light-, medium- and heavy-duty trucks; buses; heavy equipment; 4X4s; tow trucks; race cars; tractors; and motor homes.

- **Advanced protection** against wear.
- **Controls** thermal runaway.
- **Protects** against rust and corrosion.
- **Helps reduce** operating temperatures.
- **Maximum** efficiency.
- **Long** oil, seal and equipment life.
- **Flexible** Easy-Pack for clean, fast installation.

Buy Online

TYPICAL TECHNICAL PROPERTIES

AMSOIL SEVERE GEAR® Synthetic Extreme-Pressure (EP) Gear Lube

	SAE 75W-85 (SVL)	SAE 75W-90 (SVG)	SAE 75W-110 (SVT)	SAE 75W-140 (SVO)	SAE 80W-90 (AGL)
Kinematic Viscosity @ 100°C, cSt (ASTM D445)	13.3	16.0	20.5	25.9	15.5
Kinematic Viscosity @ 40°C, cSt (ASTM D445)	76.9	97.8	132.6	172.1	120.2
Viscosity Index (ASTM D2270)	176	175	179	186	135
Brookfield Viscosity, cP @ (°C) (ASTM D2983)	30,685 (-40)	61,940 (-40)	86,140 (-40)	109,000 (-40)	46,200 (-26)
Flash Point, °C (°F) (ASTM D92)	220 (428)	222 (431.6)	218 (424.4)	216 (410.8)	208 (406)
Pour Point, °C (°F) (ASTM D97)	-46 (-50)	-43 (-45)	-43 (-45)	-43 (-45)	-42 (-44)
Copper Corrosion (ASTM D130) @ 121 °C (250°F) / 3hr	1b	1b	1b	1b	1b
Foam Stability (ASTM D892)	0/0, 10/0, 0/0	0/0, 10/0, 0/0	0/0, 10/0, 0/0	0/0, 20/0, 0/0	0/0, 0/0, 0/0

For product service life in differentials, consult your owner's manual or the Original Equipment Manufacturer (OEM) to establish the application, NORMAL or SEVERE.

	Normal Service	Severe Service
Cars, SUVs, Light Trucks	Drain at **100,000** miles (161,000 kilometers) of service or according to the owner's manual, whichever is longer	Drain at **50,000** miles (80,500 kilometers) of service or according to the owner's manual, whichever is longer
Heavy-Duty Class 8 Line Haul	Follow the OEM drain interval (miles or hours) for synthetic oil up to **250,000** miles (402,500 kilometers) or three years, whichever comes first.	
Vocational/ Delivery	Follow the OEM drain interval (miles or hours) for synthetic oil up to **120,000** miles (193,200 kilometers) or three years, whichever comes first.	
Heavy-Duty Off-Road	Follow the OEM drain interval (miles or hours) for synthetic oil up to **100,000** miles or two years, whichever comes first.	

For product service life in non-differential applications, consult owner's manual or the OEM for either normal or severe synthetic oil service intervals. Where service intervals are unavailable, drain at twice the interval for conventional oil.

Gear oils should be changed more frequently when operating vehicles or equipment in dusty or dirty conditions, unless the gear system is properly sealed and equipped with membrane-type breathers.

Note: AMSOIL does not support extended drain intervals where water contamination occurs. Check and service the gear oil frequently when water contamination is possible.

AMSOIL SEVERE GEAR 75W-90, 80W-90, 75W-110 and 75W-140
Use in differentials, manual transmissions and other gear applications requiring any of the following specifications: API GL-5, MT-1, MIL-PRF-2105E, Dana SHAES 234 (Formerly Eaton PS-037), Mack GO-J or other GL-5 based specifications from vehicle manufacturers, including Ford,* GM* and Chrysler.* Can also be used in axles where an API GL-4 lubricant is recommended.

AMSOIL SEVERE GEAR 75W-85
Use in differentials, manual transmissions and other gear applications requiring any of the following specifications: API GL-5/MT-1, MIL-PRF 2105E, SAE J2360, Ford XY-75W85-QL, GM 19300457, 19418501, 92184900, 19369842, Ram 68210057AB, 68083381AA, 68364258AA, 68232947AB, 68378949AA, 05136035AC, Toyota Genuine Gear Oil LT, 08885-02506

AMSOIL SEVERE GEAR is compatible with conventional and synthetic gear oils. Mixing AMSOIL gear oil with other oils, however, will shorten the oil life expectancy and reduce its performance benefits. AMSOIL does not support extended drain intervals where oils have been mixed.

Aftermarket oil additives, other than those specified by AMSOIL, are **not recommended** for use with AMSOIL gear oil.

AMSOIL SEVERE GEAR is compatible with most limited-slip differentials. For applications that require additional limited-slip friction modifier, add AMSOIL Slip Lock.®

AMSOIL PRODUCT WARRANTY

AMSOIL products are backed by a Limited Liability Warranty. For complete information visit AMSOIL.com/warranty.aspx.

HEALTH & SAFETY

This product is not expected to cause health concerns when used for the intended application and according to the recommendations in the Safety Data Sheet (SDS). An SDS is available via the Internet at AMSOIL.com or upon request at 715-392-7101. **Keep Out of Reach of Children.** Don't pollute. Return used oil to collection centers.

*All trademarked names are the property of their respective owners and may be registered marks in some countries. No affiliation or endorsement claim, express or implied, is made by their use.

AMSOIL PROTECTION you demand. | PERFORMANCE you deserve.™

AMSOIL products and Dealership information are available from your local full-service AMSOIL Dealer.

FORMULATED, BLENDED AND PACKAGED IN THE USA

AMSOIL INC., 1 AMSOIL Center., Superior, WI 54880 • 715-392-7101 • Printed in the USA.
© 2025, AMSOIL INC. All rights reserved. The AMSOIL logo is a registered trademark of AMSOIL INC.

Buy Online